

Rock Wool Granulated



Unbonded mineral fibre in loose form that can be blown into desired areas, using a blowing machine.

Applications:

Ideal for installing around wall and floor penetrations to reduce fire pathways. As well as providing insulation to pipes and vessels where space is limited and traditional products are not suitable, fitting easily into grooves, slots, and other hard-to-reach openings. Additionally, can also be used for improving acoustical walls and floors.

Product Features:

- Quicker to install than rockwool rolls
- Low thermal conductivity
- Non-combustible, fire safe
- Corrosion resistant
- Moisture proof
- Sound-reducing

Technical Specifications:

Temperature Resistance up to	600°C
Hydrophobicity	>98%
Heat Conductivity (in normal temperature)	0.03 to 0.04 w/m-K

Availability:

IMPA	Product Description	Weight	Unit
812434	Rock Wool Granulated	10kg	Bag

Disclaimer

Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.

We're Here To Help

Have questions about the services we offer,
or enquiries about our product range?

Aste Global Pte. Ltd.
Singapore Head Office
tel. +65 6862 1212
fax +65 6897 9959
info@aste.com.sg

Aste Trading (Europe) B.V.
Rotterdam Office
tel. +31 (0)10-7470077
fax +31 (0)10-2687006
info@aste-trading.com

Aste (Shanghai) Co. Ltd.
Shanghai Office
tel. +86 021-50183908
fax +86 021-50183909
shanghai@aste-sh.com

Visit
aste.com.sg

